

Aluminium Coping



Product Description

Aluminium pressings are now a first choice material type owing to their lightweight, corrosion resistant, low maintenance and aesthetically pleasing characteristics. Typical examples are flashings, fascia's, soffits and capping's (as shown above)

Properties

Made from 1050AH14 grade aluminium sheet to BS2997 (EN612) with thickness determined by wall width,

Up to 500mm	2mm sheet
500mm +	3mm sheet.

Installation

Please refer to Trueline installation guides (for flat and sloping copings) for details.

Functional Life Expectancy:

Factory qualifies that when installed correctly and maintained in accordance with its product guidelines and O&M procedure, its products are designed to give a minimum effective functional life expectancy of 30 years.

Specification Information

Clause: H72/311 Aluminium Coping

Product: Trueline Aluminium Pressings

Manufacturer:

Handling & Storage:

Pressings and other bespoke fabrications, particularly with a polyester powder coat finish should be handled with care and should preferably be stored under cover on racks to prevent scratching. All lengths are supplied in protective polythene wrapping and components are suitably packed in boxes. If painted products are to be stored outside, cover with a tarpaulin to guard against water ingress into the protective polythene. Mill finish items should be stored undercover to avoid uneven oxidation prior to being fitted.

Maintenance:

In order to maintain proper working order, gutters should be periodically cleaned out and any built-up debris removed. Check all fixings are secure and take any remedial action to rectify if necessary. To maximise the life of the decorative paint finishes, all parts should be washed down with clean water, at least every 12 months and any damage repaired. In marine/industrial environments and dependent on distance from either the coastline or source of pollution, this period may need to be shortened to 6 or 3 months. Records of the cleaning schedule and frequency should be kept and maintained. Please enquire of our sales office, should more information be required.

Further Information

Please visit www.guttercentre.co.uk or contact the Gutter Centre team of 0330 2231731 for any other information