

New to the range

Aluminium Threaded Spigot Adaptors



facilitate the A1 fire rated connection of Harmer Roof AV and threaded aluminium rainwater outlets to all types of pipe systems. Connection is made possible by the external diameter of the spigot being equal to most standard internal pipework. The adaptor is supplied with a BS EN 10255 taper male thread, ensuring a fully watertight joint when screwed into the socket outlet and removing the requirement for a mechanical joint within the slab. High flow performance and low maintenance provide complete reassurance, which is critical to building drainage design.

Example:
One type of assembly



Benefits:

- Non-combustible A1 Fire rated spigot, A2 rated solution alongside Harmer Threaded Outlet
- Available in 2, 3, 4 and 6"
- Stocked in lengths of 400mm and 600mm
- Bespoke lengths made to order
- Easy connection to Harmer SML Soil and Vent system



Nominal Bore (mm)	a (mm)	Length (mm)	Weight (kg)	Product Code	List Price
50	58	400	0.8	2ADPA	£48.15
50	58	600	1.1	2ADPA/600	£72.22
75	82.5	400	1.15	3ADPA	£59.26
75	82.5	600	1.55	3ADPA/600	£88.89
100	110	400	1.75	4ADAP	£79.63
100	110	600	2.55	4ADPA/600	£119.44
150	160	400	2.45	6ADPA	£131.48
150	160	600	3.45	6ADPA/600	£197.22