

# PREMIER LCC SOIL

## INTRODUCTION



Hargreaves' Premier LCC Soil range provides a comprehensive offering of traditional socket & spigot pipes and fittings for soil and waste installations on the external facade of buildings with the added option to commission bespoke fabrications to special order.

Supplied ready to fit with a black bitumen finish as standard, the cast iron system offers the ideal solution for conservation and heritage projects where a pipe system is required to blend sympathetically with the building.

## SECTION CONTENTS



### Premier LCC Soil

- Eared Pipes
- Plain Pipes
- Fittings
- Ornamental Earbands
- Sundries



The image (above) shows a Premier soil system installed on a residential property alongside a Premier rainwater system.



### Availability

Most of our Premier soil products are ex-stock, however, selected items are manufactured on request. Ornamental earbands to fit LCC soil can be produced within an agreed time scale dependant on the size of the order.

## Features

---

- Pipes available from 50mm to 150mm diameters in standard lengths 0.6m, 0.9m, 1.2m and 1.8m.
- All products are based on imperial dimensions so ensuring compatibility with existing installations when replacing or extending pipework.
- Ornamental earbands are available in 9 standard designs to fit all sizes of Premier LCC soil pipes.

## Jointing

---

- Cold caulked joints can be made with 6mm caulking cord and black joint sealant both available from stock.
- This method removes the requirement for using naked flames to melt lead on site.
- Approximately 4m of caulking cord and a quarter of a cartridge of sealant would be required to make a joint in 4" diameter system.

## Strength / Durability

---

- Premier pipes are highly resistant to distortion caused by accident or vandalism
- Pipes and fittings are coated in a black bituminous coating for long term protection.

## Long Life

---

- Correctly installed and maintained Premier soil systems can last in excess of 100 years.
- Long life expectancy makes cast iron the cost effective choice.
- Minimal maintenance requirements- occasional painting approximately every 10 years (inland areas).
- 100% recyclable at the end of its life.

## Quiet in operation

---

- Low noise levels due to the sound deadening properties of cast iron.

## Bespoke

---

- Specialist castings and fabrications can be created to fit the specific requirements of your building (pattern charges may apply).
- Ears can be added to any LCC soil fitting on request.
- Over 300 variations of soil branches are offered as standard, other formations can be fabricated to fit your installation on request.

## Quality

---

- All Premier soil products are manufactured in accordance with BS416.
- Premier Soil is supplied in a durable black bitumen paint finish as standard.
- With minimal maintenance we would expect Premier soil systems to last over 100 years.

## Paint finish

---

We supply our Premier LCC soil pipes and fittings with a black bitumen finish conforming to BS 416.

Hargreaves can supply LCC soil products in Premier Extra Black Gloss or Premier Extra Coloured paint finishes to match Premier Rainwater systems on request (additional charges may apply)

If over painting please refer to your paint specialist or paint manufacturer for a compatible product.