

# ABS Shower Floor Outlets - Quality

Harmer ABS Shower Floor Outlets combine high performance, innovative design and value engineering to establish class-leading standards in drainage.

## Compliances

- Harmer Shower Floor Outlets fully meet the requirements of BS EN 1253 for general design, flow performance and load testing

## High Flow Performance

- Designed for high flow drainage with achievable flow rates of up to 1.3 litres per second (80 litres per minute)

## Robust and Secure

- Manufactured in ABS plastic compound for corrosion resistance with under-ribbed flange for extra strength
- Security fixings are also available to prevent unauthorised removal of caps

## A Choice of Caps

- The range of top accessible caps is suitable for both tiled or sheet floor applications
- Attractive mirror finish and ABS caps are available in practical plain, quadrant or pebble finishes

## Low Maintenance and Hygienic

- The antimicrobial ABS compound enhances hygiene and control of bacteria
- The efficient Harmer Shower design ensures self-cleansing flow
- The top access trap, for use with both the vertical and horizontal drain bodies, is simple to remove and replace

## Easy and Quick to Install

- Compact vertical and horizontal drain bodies install into timber and concrete floor construction
- Drain bodies are designed for direct connection to ABS solvent cement pipe systems
- Connections to PVC can be made using proprietary connectors
- Fully compatible with UK pipe sizes, where 43mm (1½"), 56mm (2") and 110mm (4") connections are required

## Value for Money

- The use of the ABS plastic compound keeps material cost low while efficiency of design ensures premium performance

## Sustainable

- ABS plastic is non toxic and 100% recyclable

