



These products are compatible with 63mmØ, 76mmØ, 102mmØ, 72x72mm, 102x76mm and 102x102mm downpipes



Gutter


Code	Nominal Length(m)	A	B
GF 413	3	120	80
GF 513	3	135	100
GF 613	3	160	100



Stop end

Code	Size		A
GF 450	120	Left Hand	33
GF 455	120	Right Hand	33
GF 550	135	Left Hand	33
GF 555	135	Right Hand	33
GF 650	160	Left Hand	33
GF 655	160	Right Hand	33


Right hand illustrated



Union


Code	Size	A
GF 420	120	70
GF 520	135	70
GF 620	160	70

Internal



Packing shim

Code	Size
SC382	120
SC381	135, 160




Fascia bracket

Code	A	B
GF 480 ¹	30	65
GF 080 ²	30	85

¹Use with 120x80 Gutter

For linear alignment use shim plate SC382


²Use with 135x100 and 160x100 Gutters
For linear alignment use shim plate SC381



Leafguard

Code	Gutter Size	A
SL 105	120x80	1220
SL 106	135x100	1220
SL 107	160x100	1220

Mill finish



Angle

Code	Size	Angle	A
GF 430	120	90° internal	185
GF 431	120	90° external	65
GF 435	120	135° internal	115
GF 436	120	135° external	65
GF 439	120	Non standard	-
GF 530	135	90° internal	200
GF 531	135	90° external	65
GF 535	135	135° internal	120
GF 536	135	135° external	64
GF 539	135	Non standard	-
GF 630	160	90° internal	225
GF 631	160	90° external	65
GF 635	160	135° internal	135
GF 636	160	135° external	69
GF 639	160	Non standard	-


Internal angle illustrated



Joint Sealant

Code	Description
SC101	310ml clear

Please note sealant shelf life is 12 months.
Refer to sealant usage table, page 57.



Outlet

Code	Size	Outlet Size	A	B	Fascia to Outlet Centre
GF 422	120	63 Ø	200	70	66
GF 423	120	76 Ø	200	70	66
GF 425	120	72x72	200	70	66
GF 426	120	102x76	200	70	66
GF 522	135	63 Ø	200	70	75
GF 523	135	76 Ø	200	70	75
GF 524	135	102 Ø	200	70	75
GF 525	135	72x72	200	70	75
GF 526	135	102x76	200	70	75
GF 527	135	102x102	200	70	75
GF 622	160	63 Ø	200	70	88
GF 623	160	76 Ø	200	70	88
GF 624	160	102 Ø	200	70	88
GF 625	160	72x72	200	70	88
GF 626	160	102x76	200	70	88
GF 627	160	102x102	200	70	88



Compatible fixing screws

Code	Description
SC201	30mm x No.10 Mill Finish For use with gutter

Environmental

Marley Alutec is committed to continually reducing its environmental impact and is accredited to ISO 14001:2004.



Handling & storage

All gutter and pipe lengths are supplied in protective polythene sleeving and components packed in cardboard boxes. If polyester powder coated products are stored outside, cover with tarpaulin to guard against water ingress. If water becomes trapped within the polythene wrapping and left exposed to warm sunlight, it may leave permanent water stains on the paint finish.



evolve RAINWATER SYSTEMS



traditional RAINWATER SYSTEMS



aligator RAINWATER SYSTEMS



evolve FASCIA, SOFFIT & COPING



elite ROOF OUTLET SYSTEMS

ALUTEC

ALUMINIUM RAINWATER SYSTEMS

For general enquiries, please call **0330 223 1731**
email: sales@guttercentre.co.uk

Unit 21 St Davids Square, Fengate
Peterborough PE1 5QA

Export Division

Telephone: **0330 223 1731**



/marleyalutec

@marleyalutec

/company/marleyalutec

marleyalutec.co.uk